



**RENDERONE**<sup>TM</sup>  
A U S T R A L I A

CLASSIC

# CLASSIC

Classic Coat (bag colour Orange)

## DESCRIPTION

- Classic Render is off white, cement based, 2 pak polymer modified classic cement render
- Can be used as a floatable finishing coat over selected Render one Skim coats and suitable substrates to achieve a Classic Traditional Render look
- Can be used as a floatable base/skim coat

## SUITABILITY

- Masonry Block
- Clay Bricks
- Hebel Panels/Blocks
- Cement Sheet
- Cement Panels
- Polystyrene Sheets(not as a base coat)
- Tiles
- PVC
- Painted Surfaces

## SPECIAL FEATURES

- Water soluble, easy to clean and environmentally friendly
- Easy to apply and fast to finish
- Superior adhesion eliminating drumminess and delamination
- Can be applied to damp substrates
- Excellent impact and mechanical strengths
- Minimal shrinkage
- Self priming to substrate
- Can be coated with a paint or membrane 48 hours after completion

## SURFACE PREPARATION

All surfaces to be free of oil, dust, loose mortar prior to application

# CLASSIC

Classic Coat (bag colour Orange)

## MIXING DIRECTIONS

1. All Render One Classic Render twill be mixed with a 6:1 water polymer ratio when applied at a thickness less than 10mm  
*NB: no polymer required when applied beyond 10mm thick*
2. Pour approximately four and a half (4.5) litres of the diluted Render One polymer into a clean empty 15 litre pail
3. Gradually add the selected Render One Classic Render and mix with a variable speed/high torque mixing drill fitted with a suitable spiral mixer.  
*NB: Over mixing of high speed mixing may cause aerating which can affect usability.*

## APPLICATION GUIDE

Mix thoroughly to a workable consistency and apply to substrate using hawk and trowel or approved render spray pumps over Render One Skim coats or suitable substrates

### **Applied over Render One Skim Coats:**

1. Apply Classic Render to a thickness of approximately 2mm-4mm
2. Float product utilizing a circular arm motion with a plastic trowel, plastic Diamond Float and or Render sponge to achieve a Classic Traditional seamless Render finish

### **Applied to suitable substrate as a base coat:**

1. Classic Render can be used as a self priming, floatable base/finish coat that can be built up to a thickness of 12mm using correct application methods.
2. Product can then be floated or leveled with a suitable screed or straight edge to alleviate any hollows or defects.
3. Finish using a plastic trowel, plastic diamond float, wooden float and /or render sponge, float with a circular arm motion, to achieve a Classic Traditional Seamless Render.

Average Thickness	4mm	6mm	8mm	8-12mm
Coats	1	1	1-2	2

# CLASSIC

Classic Coat (bag colour Orange)

## PAINTING GUIDE

Allow at least 48 hours to dry before painting

Paint with two (2) coats of a high quality acrylic membrane or paint

## GUARANTEE

Ten year guarantee when applied by an approved applicator to Render One Specifications

## HOW TO

Specification Classic Render as a Finish Coat

1st Coat	Apply Render One:	Regular gauge skim Max gauge skim coat
2nd Coat	Apply Render One Classic Render	
3rd Coat	Apply One Coat of High Grade acrylic paint or membrane	
4th Coat	Apply One Coat of High Grade acrylic paint or membrane	



CLASSIC